



 A range of Yellow Brass threaded fittings.

Features and Benefits:

- Yellow brass threaded fittings.
- Available in sizes 1/8 - 2".
- Manufactured to BS EN 1254-4.
- The threads are manufactured to ISO 228-1.
- Suitable to material with EN12165, CW617N, EN12164 and CW617N.
- Hydraulic working temperatures and pressures:

Size (inches)	Working pressure (bar)	
	-20°C to 120°C	>120 to 225°C
1/8" to 3/4"	25	16
1 to 2	16	10
2 to 4	10	6



8000 Range

Brass Plug
Male Thread (Parallel)



8595

From: 1/4"
To: 2"

Female Elbow
Female x Female Thread



8090

From: 1/4"
To: 3/4"

Male x Female Elbow
Male x Female Thread



8092

From: 3/8"
To: 1"

Tee - Equal
Female Thread All Ends



8130

From: 1/4"
To: 1"

Reduced Bush
Male x Female Thread



8241

From: 3/8" x 1/4"
To: 2" x 1.1/2"

Straight Coupler
Female x Female Thread



8270

From: 1/4"
To: 2"

Hexagon Nipple
Male x Male Thread



8280

From: 1/8"
To: 2"

Flanged Backnut



8310

From: 1/2"
To: 2"

Barrel Nipple Male
Thread x Length (mm)



8530

From: 3/8" x 40mm
To: 2" x 100mm


Running Nipple
Male (Parallel)



8531

From: 1/4"
To: 3/4"

Blank Cap
Female Thread



8599

From: 1/4"
To: 2.1/2"



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 557 0185 | Email: sales@ibpgroup.com | Website: www.conexbanninger.com

an IBP GROUP company

This is a representation of the full range from Conex Universal. IBP trade marks are registered in numerous countries.